

XXLS 10" Subwoofer



Type Number: 830842

Features:

This new series of state-of-the-art subwoofers continue to enhance Peerless' reputation for delivering the highest quality components for bass in the world. Called the XXLS - for "Xpanded Extra Long Stroke" - these new audio transducers add even more excursion to the Peerless XLS line, and completely eliminate distortion.

Driver Highlights: Thick Nomex cone, 51 mm voice coil, ALP

[Go to Application Notes.](#)

[Go to Architecture Notes](#)



Specs:

Electrical Data

Nominal impedance	Zn	4	ohm
Minimum impedance	Zmin	3.9	ohm
Maximum impedance	Zo	122.5	ohm
DC resistance	Re	2.6	ohm
Voice coil inductance	Le	4.2	mH
Capacitor in series with x ohm	Cc	--	uF

T-S Parameters

Resonance Frequency	fs	19.2	Hz
Mechanical Q factor	Qms	8.74	
Electrical Q factor	Qes	0.19	
Total Q factor	Qts	0.19	
Ratio fs/Qts	F	103	
Force factor	Bl	14.9	Tm
Mechanical resistance	Rms	1.84	Kg/s
Moving mass	Mms	133.8	g
Suspension compliance	Cms	0.52	mm/N
Effective cone diameter	D	21.2	cm
Effective piston area	Sd	352	cm ²
Equivalent volume	Vas	88.4	ltrs
Sensitivity		88.4	dB
Ratio BL/√(Re)		9.2	


Power handling

100h RMS noise test (IEC)	175	W
Long-term Max System Power (IEC)	350	W
Max linear SPL (rms) @ power	--	dB/W
Short Term Max power	--	W

Voice Coil and Magnet Parameters

Voice coil diameter	51	mm
Voice coil height	33	mm
Voice coil layers	4	
Height of the gap	8	mm
Linear excursion +/-	12.5	mm
Max mech. excursion +/-	--	mm
Flux density of gap	--	mWb
Total useful flux	2.3	mWb
Diameter of magnet	147	mm
Height of magnet	35	mm
Weight of magnet	2.4	Kg

Frequency:



Mechanical Dimensions:

